



## Risk Assessment Panther Vario Jib

The people that might be harmed: Studioworks employees, contractors, public, artists

HAZARD	CONTROL
<ul style="list-style-type: none"><li>• Injury through manual handling</li><li>• Jib may become unstable or overturn</li><li>• Camera may become detached from its retaining bracket/mount</li><li>• Jib may hit something</li><li>• Finger/hand trap, crush injury</li><li>• Hitting obstructions during Jib movement.</li><li>• Contact resulting in Jib or obstruction becoming unstable.</li><li>• Injury to others from physical contact with moving parts of jib or something falling from the jib</li></ul>	<ul style="list-style-type: none"><li>• Experienced, trained and competent person in control of assembly and operation.</li><li>• The Jib Arm must be placed on a Level mounting.</li><li>• The Jib Arm must be supported at the front during rig/derig.</li><li>• A wire safety bond should be threaded through handle of camera and attached to camera bracket/mount to prevent camera falling any other items that may become detached (lens, viewfinder, etc) should be separately bonded or removed.</li><li>• The operator and others involved in the rigging and use of the crane/jib are experienced in the assembly and operation of this particular apparatus in the required configuration and in similar operating circumstances.</li><li>• Crane/jib should either be placed on a level Track / platform constructed using approved materials and in an appropriate fashion.</li><li>• Make aware to others in the vicinity of the jibs movements or set up an exclusion zone.</li></ul>

File: Panther Vario Jib

Version: Version 1.1

Last Reviewed: 05/07/2023